



701 S Ridge Avenue, Troy, OH 45374
1-888-4HOBART • www.hobartcorp.com

PLUGS AND RECEPTACLES FOOD MACHINES



PLUGS AND RECEPTACLES FOOD MACHINES

MACHINE VOLTAGES										
Service Current Requirement if Plug Connected	120/60/1	200/60/1 208/60/1	230/60/1	200-240/ 50/60/3/1	200/60/3 or 208/60/3			230/60/3		460/60/3
	15 Amp.		15 Amp.	20 Amp.	20 Amp.	30 Amp.	30 Amp.	20 Amp.	30 Amp.	20 Amp.
Terminal Designation of Plug	2 Pole 3 Wire Grdg.		2 Pole 3 Wire Grdg.		4 Pole 5 Wire Grdg.	3 Pole 4 Wire Grdg.	4 Pole 5 Wire Grdg.	3 Pole 4 Wire Grdg.	3 Pole 4 Wire Grdg.	3 Pole 4 Wire Grdg.
NEMA Plug Configuration	5-15P		6-15P		L21-20P	L15-30P	L21-30P	L15-20P	L15-30P	L16-20P
Plug Configuration										
Molded Plug on Cord	Yes		Yes		No		No	No	No	No
Plug-Straight/Angle	Straight		Straight		Straight		Straight	Straight	Straight	Straight
NEMA Receptacle or Connector Configuration	5-15R		6-15R		L21-20R		L21-30R	L15-20R	L15-30R	L16-20R
Choppers	4812	X	X		✓			✓		✓
	4822	X			✓			✓		✓
	4732/4732A		✓	✓			X ▲		✓	✓
Cutter Mixer	HCM450						X		X	X
Fat Tester	F101	X	X							
Food Cutter	84145	X	X		X					
	84186	X	X		X					X
Food Processors	FP41	X								
	HCM61	X *								
	HCM62							X		
	FP100	X								
	FP150	X								
	FP250	X								
	FP350	X								
	FP400						*	X		
Grinders	4146						✓		✓	✓
Mixer Grinders	4246					X				X
	MG1532					X				X
	MG2032					X				X
Mixers	N50	X	X							
	HL120	X	X							
	HL200	X		X						
	HL300	X	200-240	X				200-240		380-460
	HL400		200-240	✓				200-240		380-460
	HL600/ HL662				✓			200-240		380-460
	HL800							200-240		380-460
	HL1400/ HL1400N							200-240		380-460
Peelers	6115	X	X							
	6430/6460				Available 208-240/60/1 - No Cord			208-240/60/3 - No Cord		
	6460M				Available 208-240/60/1 - No Cord			208-240/60/3 - No Cord		

X Cord and Plug Standard ▲ Available as an option — not UL Listed
* See notes column ✓ Available at specified voltage no cord and plug available

PLUGS AND RECEPTACLES FOOD MACHINES



701 S Ridge Avenue, Troy, OH 45374
1-888-4HOBART • www.hobartcorp.com

MACHINE VOLTAGES (continued)

Service Current Requirement if Plug Connected	120/60/1	200/60/1 208/60/1	230/60/1	200/60/3 or 208/60/3			230/60/3		460/60/3
	15 Amp.		15 Amp.	20 Amp.		30 Amp.	20 Amp.	30 Amp.	20 Amp.
Terminal Designation of Plug	2 Pole 3 Wire Grdg.		2 Pole 3 Wire Grdg.	4 Pole 5 Wire Grdg.		4 Pole 5 Wire Grdg.	3 Pole 4 Wire Grdg.	3 Pole 4 Wire Grdg.	3 Pole 4 Wire Grdg.
NEMA Plug Configuration	5-15P		6-15P	L21-20P		L21-30P	L15-20P	L15-30P	L16-20P
Plug Configuration									
Molded Plug on Cord	Yes		Yes	No		No	No	No	No
Plug-Straight/Angle	Straight		Straight	Straight		Straight	Straight	Straight	Straight
NEMA Receptacle or Connector Configuration	5-15R		6-15R	L21-20R		L21-30R	L15-20R	L15-30R	L16-20R
Power Drive	PD35/70	X							
Salad Dryers	SDPE	X	X						
	SDPS	X	X						
Saws	6614	✓		Available 208-240/60/1 - No Cord		208-240/60/3 - No Cord			
	6801		✓	Available 208-240/60/3 - No Cord					
Slicers	Edge12	X	X						
	HS6	X	X						
	HS7	X	X						
	HS8	X	X						
	HS9	X	X						
Tenderizer	403	115/60/1							
Vegetable Cutters	M2000	X							
	M3000	X	X						

X Cord and Plug Standard ▲ Available as an option — not UL Listed
* See notes column ✓ Available at specified voltage no cord and plug available

PLUGS			RECEPTACLES OR CONNECTORS				
NEMA Plug Configuration	Hubbell Part No.	Woodhead Part No.	NEMA Receptacle or Connector Configuration	Hubbell Part No.		Woodhead Part No.	
				Receptacle	Connector	Receptacle	Connector
5-15P	5266-C	—	5-15R	5262	5269-C	—	—
6-15P	5366-C	—	6-15R	5362	5669-C	—	—
L21-20P	2511	—	L21-20R	2510	2513	—	—
L21-30P	2811	—	L21-30R	2810	2813	—	—
L15-20P	2421	26W75	L15-20R	2420	2423	67W75	27W75
L15-30P	2721	28W75	L15-30R	2720	2723	69W75	29W75
L16-20P	2431	26W76	L16-20R	2430	2433	67W76	27W76

As continued product improvement is a policy of Hobart, specifications are subject to change without notice.